PETROLEUM CONTAINMENT, INC.

Penetration Fittings

Split Repair Fittings (SRF Series)

Easily replace leaking rubber and plastic penetration fittings with a fiberglass fitting without disconnecting pipe. We manufacture durable, cost effective fiberglass repair fittings that are easy to install with out the need of cumbersome band clamps.

Our fiberglass construction replaces the use of rubber boots therefore preventing leakage and providing long term solution. Featuring large outside diameter to cover existing pipe entry holes.

Features and Benefits

REPAIR PENETRATION FITTING

Cam-Lock Design
A simple quarter turn holds the fitting in place while the epoxy cures. No aggravating band clamps are necessary.

Fiberglass Construction
Will withstand long-term exposure to all fuels, including ethanol.

Allows Misalignment
Works with angled pipe entries up to 20°.

Cost Effective
Similar cost as most rubber or plastic fittings.

Long-Term Solution
Never replace a penetration fitting again.

PF-SRF-3F-R3

Ordering Information

SRF Model	Flat Wall	Round Wall	I.D.	O.D.
Galv Conduit 3/4”	PF-SRF-3F-C8	PF-SRF-3R-C8	1.1”	4.5”
Galv Conduit 1”	PF-SRF-3F-C1	PF-SRF-3R-C1	1.4”	4.5”
Fiberglass Pipe 2”	PF-SRF-3F-R2	PF-SRF-3R-R2	2.4”	6.5”
Fiberglass Pipe 3”	PF-SRF-3F-R3	PF-SRF-3R-R3	3.6”	7.5”
Fiberglass Pipe 4”	PF-SRF-3F-R4	PF-SRF-3R-R4	4.6”	8.5”
LCX Pipe 2”	PF-SRF-3F-L2	PF-SRF-3R-L2	2.7”	6.5”
LCX Pipe 3”	PF-SRF-3F-L3	PF-SRF-3R-L3	3.8”	7.5”
LCX Pipe 4”	PF-SRF-3F-L4	PF-SRF-3R-L4	4.8”	8.5”

c UL us LISTED UL2447